



6



Bezel Lens Dial Indication wheel Counter wheel Housing Mounting Connections Illumination

:metal (CuZn37), black, triangular vers :glazing glass, nonreflective :black background with white character :red :5x black with white figures,1x white :plastic (PBT S650), flame retardant :clamp ring, plastic (PBT) :blade terminals 6.3 x 0.8 mm, DIN 4 :LED, white

Technical Data:

Operating voltage Indication accuracy Maximum hours Current consumption: Protection: Storage temperature: 8 V - 32 V $\pm 5 s per day, - 40 °C to + 85 °C:$ 999999,9 h max. (nonresettable) $<math>\pm 13,5 V: < 10 mA at room temperature:$ <math>19 65 frontside, IP42 rearside $\pm 26,0 V: < 23 mA at room temperature:$ - 40 °C to + 90 °COperating temperature:<math>40 °C to + 85 °C

6

| | 9 10 11 NOTES | 12 |
|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | А |
| LABEL 89 TX | CONTINENTAL EH A2CI9362500 12/24 DD.MM.YY XXXX CE_1 IOR-XX XXX | |
| | (AB) 'Company name' 'Brand name' 'Article number' 'voltage' 'Production date' 'serial number' | C |
| | | D |
| | | E |
| | AB 5 - Storage and operating temperatures: 'to' instead of 'bis' | |
| | 3)Remove Germany text 4)Add calulated weight | es), ' instead of 'bis', es' instead of 'Zweimal', |
| ers | DOC. VERS. CHANGED ITEMS ZONE IN GRID CHANGE DESCRIPTION ECM NO. 1040010 CREATED BY Noordin.Hasni CHANGE DESCRIPTION DATE 2020-02-06 DATE VNI VNI 2020-02-06 DATE VNI OPATE 2020-02-06 DEPAF VNI VNI VNI REVIEWED BY Mohd.Salleh.Mahfuz DATE 2020-02-06 DEPAF VNI VNI DATE | es' instead of 'bis', es' instead of 'Zweimal', <u>4PEP:007901</u> 08 RTMENT <u>CVS AE MYS ME</u> RTMENT CVS AE MYS ME RTMENT |
| ers e with red figures (1/10h-wheel) | DC. Change tablet into 3)Remove Germany text 4)Add calulated weight 5)Add spinlock nut DC. CHANGED ZONE IN ITEMS CHANGE DESCRIPTION ECM NO. 1040010 CREATED BY Noordin.Hasni CHANGE DESCRIPTION DATE DEPAR 2020-02-06 DATE REVIEWED BY Mohd.Salleh.Mahfuz DATE DEPAR 2020-02-06 DATE DEPAR 2020-02-06 DATE RELEASED BY Mohd.Zawawi.Shamsuzaili DATE DEPAR 2020-02-06 DATE DEPAR 2020-02-06 DATE TITLE Hourmeter - - - - - | 25), ' instead of 'bis', es' instead of 'Zweimal', <u>4PEP:007901</u> 08 RTMENT <u>CVS AE MYS ME</u> RTMENT <u>CVS AE MYS ME</u> RTMENT <u>CVS AE MYS ME</u> |
| ersion ters e with red figures (1/10h-wheel) 46244 (reverse-polarity protection) : max10 s per day erature perature | DOC. CHANGED ZONE IN SINGHOVE GERMANY text 4)Add calulated weight S)Add spinlock nut DOC. CHANGED ZONE IN GRID CHANGE DESCRIPTION CREATED BY DATE DPATE Noordin.Hasni DATE DPATE Mohd.Salleh.Mahfuz DATE DEPAF Mohd.Zawawi.Shamsuzaili DATE DEPAF TITLE DATE DEPAF Mourmeter - DATE DEPAF | 25), ' instead of 'bis', es' instead of 'Zweimal' 4PEP:007901 08 RTMENT CVS AE MYS ME RTMENT CVS AE MYS ME RTMENT CVS AE MYS ME RTMENT CVS AE MYS ME RTMENT CVS AE MYS ME (G AB WEIGHT - <u>g ± - %</u> |